


NOTES:

1. ELECTRICAL: 120-277 VAC, 1PH, 50/60Hz
2. CONFORMS TO HAZARDOUS AREA RATING:
 1. ATEX/IECEX Ex db IIA T3 Gb
 2. UL CLASS I, DIV 1, GROUP D T3
3. ENCLOSURE : TYPE 4, HORIZONTAL OR VERTICAL MOUNT
4. RELIEF VALVE SET: 250 PSIG [17,24 BAR]
5. MAWP: 250 PSIG AT 300°F [17,24 BAR AT 149°C]
 MDMT: -20°F AT 250 PSIG [17,24 BAR AT -29°C]
6. WEIGHT: 50 LB [23 KG]
7. DIMENSIONS SHOWN IN INCHES [MM]



DO NOT SCALE DRAWING

INTERPRET THIS DRAWING IN ACCORDANCE WITH ANSI/ASME Y14.5-2009.
 THIS DRAWING IS PROPRIETARY AND CONFIDENTIAL AND SHALL NOT BE REPRODUCED OR USED IN ANY MANNER DETRIMENTAL TO ALGAS-SDI'S INTERESTS. ALL RIGHTS RESERVED. © COPYRIGHT ALGAS-SDI

TOLERANCES
 UNLESS OTHERWISE SPECIFIED
 .X ± 0.10
 .XX ± 0.030
 .XXX ± 0.010
 ANGLE ± 1°
 FRACTIONS ± 1/4"

151 S. Michigan St., Seattle, Washington, USA 98108
 Tel: (206) 789-5410 Fax: (206) 789-5414

Part # **N/A**

Drawn By:	AAS
Checked By:	
Approved By:	
Date:	1/29/2018
Scale:	1:8 AND NOTED
Job #	ASDI STD

Title: Z25, Z40 & Z50 EQUIPMENT DRAWING	
Size: B	Dwg. # 0903-6001
Sht. No.: 1 of 1	Rev.: C